

Thanking you,

*७*७। पिर्चियास्यामुनाकाःजन्नःपह्नया।

Bhutan Power Corporation Limited

(An ISO 9001:2015, ISO 14001:2015 &ISO 45001:2018Certified Company)
Registered Office, Thimphu
Thimphu: Bhutan



104/BPC/C&PD/CM	S/2023/VoI -1/	March 10, 2023
Subject: Bid Document: Dear Sir,	Amendment No. 2 BPC/C&PD/CMS/TENDER-2023/06 (Labworks under Samdrup Jongkhar, Sarpar Dzongkhag)	
This amendmen	t is being issued to incorporate the change which is enclosed as Appendix 1.	es in the price schedule for
Therefore, the bidder terms and conditions	es are advised to note the above changes and remain unchanged.	quote accordingly. All other
Please confirm the re	ceipt of this Addendum by return mail/fax to	the CMS, CD, C&PD, BPC.

Yours sincerely,

(Dorji Kinley)
Senior Manager

Address:

Contracts Management Section, Construction Division, Construction & Procurement Department, Bhutan Power Corporation Ltd.,

Thimphu: Bhutan

Telephone /Website/ Email:

Phone: +975- 2-322046 (Direct) Phone: +975-2-325096 (Ext: 774)

Website: www.bpc.bt

Email:dorjikinley@bpc.bt /cmsection@bpc.bt

Registered Office:

Bhutan Power Corporation Ltd.,

PO Box: 580, Thimphu: Bhutan



Price Schedule

Package DW23-N1

Deposit works under Thimphu Dzongkhag

Item No.	vorks under Thimphu Dzongkhag		7 4 1		
		Unit	Quantity	Rate (Nu.)	Amount (Nu.)
_!	Power Supply extension to Barshong BTS under Naro Gewog	1		-	
_A	MV Line (ACSR Bare conductor)				
	Detailed route survey, clearing of jungle/bushes, felling of trees including cutting of				
	trunks, branches & removing the trees (especially blocking of foot path & roads),				
1	transportation of materials both head loading and vechicular from the stores to sites,				11
	digging of holes, erection of poles, laying and stringing of conductors, fittings and				
	accessories, testing, commissioning and any other associate works				
1.1	11kV lines (ACSR bare conductor) with Galvanized Steel Tubular Pole 10 m				
a	Rabbit conductor (3 phase 3 wire)	Km	1.80		
В	LV Line (ABC conductor)	Kill	1.00		
	Low Voltage Line (ABC) with Galvanized Steel Tubular Pole 7.5 M - Tashiling &				
1.2	Gerwa BT Tower				
			0.04		
_ a	For 4C, 95 Sq. mm	Km	0.04		
_C	Substation Construction				
	Detailed route survey, clearing of jungle/bushes, felling of trees including cutting of				
	trunks, branches & removing the trees (especially blocking of foot path & roads),				
	transportation of materials both head loading and vechicular from the stores to sites,				
1.3	digging of holes, erection of poles, supply of miscellaneous items such as nut & bolt,				
	lugs, etc., installation of transformer, fittings and accessories, installation of GEE			1	
	earthing slab, painting of poles, concreting of pole base, testing, commissioning and				
	any other associate works				
a	Three phase Transformer 11/0.415 kV - 25 kVA	Nie	1.00		
		No	1.00		
b	Erection and installation of 3P Dist.Board 4W 63A MCCB with 32A HRC	No	1.00		
	Sub-Total for I				
11	Power supply to Integrated Waste Management Facility (NEC) at Memelakha		11	and the state of	
	under Chang Gewog, Thimphu Dzongkhag				
A	Medium Voltage Lines and Low Voltage Lines (OH)				
	Detailed route survey, clearing of jungle/bushes, felling of trees including cutting of trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vechicular from stores to sites, digging of holes, erection of poles, laying and stringing of conductors, fittings and accessories, HV ABC cable termination kit jointings, supply of miscellaneous items such as nut & bolt, lugs, etc., modification of fittings like drilling, welding, etc., testing, commissioning and any other associated works.		ć.		
1.1	11kV lines (HV ABC conductor) with GI Steel Tubular Poles 10m				
	6.35/11kV grade, 3 C x 300 sq.mm	КМ	1.50		
a	Detail route survey, clearing of jungle/bushes along the RoW, rivers, footpath and	IXIVI	1.30		
1	roads etc., transportation (both headloading and vehicular) from stores to sites, road/drain/trench cutting & reinstatement wherever necessary, laying of cable in the trench/duct and with HDPE/Hume pipe of required size at road/drain crossing, supply of miscellaneous items such as nut & bolt, lugs, etc., to complete the work in full as per the approved drawings.				,
1.1	11kV grade, 3 core x 300 sq.mm	Mtrs.	250.00		
	Termination of indoor/outdoor termination kit (heat shrink) and other accessories to				
1.2	complete the work in all respect				
a	11kV grade, 3 C x 300 Sq.mm	Set	10.00		
В	LV Line (ABC conductor)				
2.1	Low Voltage Line (ABC) with Galvanized Steel Tubular Pole 10 M				
a	For 4C, 95 Sq. mm	Km	1.50		
2.2	Detail route survey, clearing of jungle/bushes along the RoW, rivers, footpath and roads etc., transportation (both headloading and vehicular) from stores to sites, digging of trench (0.5m width & 750mm depth) for direct burial, road/drain cutting & reinstatement wherever necessary, laying of cable including HDPE/Hume pipe of required size at road/drain crossing, cable terminations, supply of miscellaneous items such as nut & bolt, lugs, etc., to complete the work in full as per the approved drawings.		113/0		
	such as not a bolt, lugs, etc., to complete the work in full as per the approved drawings.	l			



C Installation of RNU Detailed sets survey, clearing of jungle/bushes, felling of trees including cutting of trunks, branches & removing the trees (especially blocking of foot path & roads), earth work in execution over areas & disposal of executed earth, transportation of materials both head loading and verhicular from stores is site, installation of RNU, laying of Catelabe between RND & transformer, earthing connections, supply of miscellaneous sites as she as not & Bold, lug, etc., testing & commissioning of RNU and movement of the stores to sites, stallation of Construction D Sabstation Construction D Catalled rous survey, clearing of jumple/bushes, felling of trees including cutting of trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and veclicular from the stores to sites, digging of holes, crection of poles, supply of miscellaneous items such as nut & bolt, lugs, etc., installation of ransformer, flutings and accessories, installation of GEE earthing slab, painting of poles, connecting of pole base, testing, commissioning and any other associate works. a Three phase Transformer 110.41 S kV - 1250 kVA b Three phase Transformer 110.41 S kV - 1250 kVA c Exection and installation of 3P Dist Board 800630 A with HRC Fuse C Construction of Transformer Printh - 2 nos. 2.1 Use, on on plan, including and poles of dains not exceeding 1.5m in width or area to be a store of the store of anism sort exceeding 1.5m in width or area to be a store of the store of th					· · · · · · · · · · · · · · · · · · ·
trunks, branches & removing the trees (especially blocking of foot path & roads), earth work in executation over areas & disposed of exvarided earth, transportation of materials both head loading and verkicular from stores to sites, installation of RNU, laying of collede between RNU & transformer, extring connections, supply of miscellaneous terms such as nut & both, lugs, etc., testing & commissioning of RNU and miscellaneous terms such as nut & both, lugs, etc., testing & commissioning of RNU and and other associated works. D. Sabstation Construction D. Datablet for outcurvey, cleaning of jumple/bushes, felling of frees including cutting of runks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vechicular from the stores to sites, digging of holes, creation of poles, supply of miscellaneous tiems such as nut & both, lugs, etc., installation of removement of poles, concreting of pole base, testing, commissioning and any other associate works. a Three phase Transformer 110.415 k.V - 1250 k.V.A b Three phase Transformer 110.415 k.V - 1250 k.V.A c Terection and installation of 3P Dist Board 800030 A with HRC Fuse E Construction of Transformer Planth - Zaos. Exercation in foundation foundation sets in high systems of the planth - Zaos countries and shutteri	С	Installation of RMU			
laying of cables between RMU & transformer, earthing connections, supply of miscellaneous items such as nut & bolt, lugs, etc., testing & commissioning of RMU and any other associated works. 11kV RMU No 1.00 Detailed route survey, clearing of jungle/bushes, felling of trees including cutting of trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vechicular from the stores to sites, digging of holes, erection of poles, supply of miscellaneous items such as nu & bolt, lugs, etc., installation of GEE carthing slab, painting of poles, concreting of pole base, testing, commissioning and any other associate works. 1 Three phase Transformer 110.415 kV - 1250 kVA 1 Three phase Transformer 110.415 kV - 1250 kVA 2 Three phase Transformer 110.415 kV - 1500 kVA 2 Fection and installation of 3P Dist Board 800/430 A with HRC Fuse E Construction of Transformer Plinth - 2nos. Examination in foundation transhes or drains not exceeding 1.5m in width or area 1 losg m on plan, including dressing & ramming, disposal of surplus soil with in 50m lead. & 15 mill-11ard soil on & 18 in 15 mill-11	,	trunks, branches & removing the trees (especially blocking of foot path & roads), earth work in excavation over areas & disposal of excavated earth, transportation of			
A D. Substation Construction Detailed route survey, clearing of jungle/bushes, felling of trees including outling of trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vehicular from the stores to sites, logis of holes, erection of poles, supply of miscellaneous incurs when the both logs, etc., installation of transformer, fittings and accessories, installation of GEE earthing slab, painting of poles, concreting of pole base, testing, commissioning and any other associate work. a Three phase Transformer 110.415 kV - 1250 kVA No 1.00 E Three phase Transformer 110.415 kV - 1250 kVA No 1.00 E Construction of Transformer Plinth-15 kV - 1250 kVA E Construction of Transformer Plinth-12 cos. Lead & 1.5m lift-llard soil 1. log am on plan including dressing & ramming, disposal of surplus soil with in 50m lead & 1.5m lift-llard soil 2. Elimpstrenches, sucksoffoundationsete inlayers-200musing selected exeavated carbinate and the survey of the s	1	laying of cables between RMU & transformer, earthing connections, supply of miscellaneous items such as nut & bolt, lugs, etc., testing & commissioning of RMU and			
Detailed route survey, clearing of jungle/bushes, felling of trees including cutting of trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vechicular from the stores to sites, diagnostic of poles, carporting of poles, carporting of poles can be bush lugs, etc., installation of poles, supply of miscellaneous insms such as nut & both, lugs, etc., installation of poles, conventing of pole base, testing, commissioning and any other associate works a Three phase Transformer 11/0.415 kV - 1250 kVA b Three phase Transformer 11/0.415 kV - 500 kVA c Fercetion and installation of 3P Dist Board 800/630 A with HRC Fuse C Construction of Transformer Pilith - 200s. Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area Excavation in foundation tranches or drains not exceeding 1.5m in width or area 2. Fillinge/frenches. sidesoffoundationsetc inlayers-200mmusingselected excavated carth. ramming etc. within lead 50 m & lift 1.5m carthyling and laying land packed store filling or soling with stones cum 0.74 2. Providing and laying land packed store filling or soling with stones cum 0.74 2. Providing a laying in position palan tement concrete excluding the cost of centering stone providing a layin			No	1.00	
Detailed route survey, clearing of jungle/bushes, felling of tress including cutting of trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vechicular from the stores to sites, digging of holes, erection of poles, supply of miscellaneous items such as nu & both, bugs, etc., installation of prosports, concreting of pole base, testing, commissioning and any vother associate work. a Three phase Transformer 110.415 kV - 1250 kVA No 1.00 b Three phase Transformer 110.415 kV - 500 kVA No 1.00 c Frection and installation of 3P Dist Board 800630 A with HRC Fuse No 2.00 Executive to infoundation transformer Plinth - 2nos. Execution in foundation transformer Plinth - 2nos. Execution in foundation transformer arises in the state of the provision in foundation transformer plinth - 2nos. I shall fill-ind solid metables of arises not exceeding L5m in width or area to see that the state of the stat			140	1.00	
trunks, branches & removing the trees (especially blocking of foot path & roads). transportation of materials both head loading and vecleular from the stores to sites, digging of holes, crection of poles, supply of miscellaneous items such as nut & bolt, lugs, etc., installation of transformer, fittings and accessories, installation of GEE earthing slab, painting of poles, concreting of pole base, testing, commissioning and any other associate works a Three phase Transformer 110.415 kV - 1250 kVA No 1.00 b Three phase Transformer 110.415 kV - 500 kVA No 1.00 c Erection and installation of 3P Dist Board 800/300 A with HRC Fuse No 2.00 E Construction of Transformer Plith - 2nos. Excavation in foundation tranches or drains not exceeding 1.5m in width or area 105 m or plan, including dressing & ramming, disposal of surplus soil with in 50m lead & 1.5m life1 lard soil card and shartering - All two-flat plans of the state of the card and shartering - All two-flat plans of the state of the card and shartering - All two-flat plans of the state					
a Three phase Transformer 11/0.415 kV - 1250 kVA No 1.00 b Three phase Transformer 11/0.415 kV - 500 kVA No 1.00 c Frection and installation of 3P bits Board 800/630 A with HRC Fuse No 2.00 E Construction of Transformer Plinth - 2nos. Excavation in foundation transhes or drains not exceeding 1.5m in width or area 2.1 losq men plan, including dressing & ramming, disposal of surplus soil with in 50m lead & 1.5m lift-lard soil lifted providing and laying the sing & ramming, disposal of surplus soil with in 50m lead & 1.5m lift-lard soil Providing and laying prosition plan incement concrete excluding the cost of centering and shuttering - All work upto plinth level. 1:3:6 (1 cement : 3 sand : 6 graded crushed crock 20 mm nominal size) Providing & laying in position plan cement concrete excluding the cost of centering and shuttering - All work upto plinth level. 1:3:6 (1 cement : 3 sand : 6 graded crushed rock 20 mm nominal size) Providing & laying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 Providing & Isying genositionerinforcedecementconcreteexcludingthecostofcentering-shut crimgandre-inforcement-all-workupfolinth level Providing & Isying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 Providing & Isying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 Providing & Isying centering and shuttering (formwork), including strutting, propping etc. and removal of formwork 2.8 Mechanically Treatedrein forcementbar (YieldStrength500MPa)forR.C.Cworkincluding cutting. Mediang-binding and placing in position complete cutting-hending-binding and placing in position complete 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq. 19.28 F Construction of chain link fence (10mX10m) with gate - 2nos. Excavationinfoundatontrenchesorderainsnotexeeding Lismiwodthorarea10sq.monpla noiludingdressing&rmming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil Providing & laying cement concrete 150mm thick (1:48), 40 mm agg. excluding	1.3	trunks, branches & removing the trees (especially blocking of foot path & roads), transportation of materials both head loading and vechicular from the stores to sites, digging of holes, erection of poles, supply of miscellaneous items such as nut & bolt, lugs, etc., installation of transformer, fittings and accessories, installation of GEE earthing slab, painting of poles, concreting of pole base, testing, commissioning and			
b Three phase Transformer 11/0.415 kV - 500 kVA	a		No	1.00	
C Erection and installation of 3P Dist Board 800/630 A with HRC Fuse No 2.00 E Construction of Transformer Plinth - 2nos. Excavation in foundation tranches or drains not exceeding 1.5m in width or area 10sq m on plan, including dressing & ramming, disposal of surplus soil with in 50m lead & 1.5m lift-llard soil 11lingoffrenches, sidesoffoundationsetc inlayers<200mmusingselected excavated earth, ramming etc. within lead 50 m & lift 1.5m 2.3 Providing and laying Hand packed stone filling or soling with stones Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level, 1:3.6 (1 cement : 3 sand : 6 graded crushed rock 20 mm morimal size) 2.5 Providing & laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level, 1:3.6 (1 cement : 3 sand : 6 graded crushed rock 20 mm morimal size) 2.5 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 2.6 Providing & living centering and shuttering (formwork), including strutting, propping etc. and removal of formwork Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, bending, binding and placing in position complete 2.10 Supplying/collection and stacking of stone agergate-20 mm 3.21 Section of chain link fence (10mx10m) with gate - 2nos. Excavationifoundation renchesor/anisnotexeedingle5minwidthorareal 10sq.monpla, nincluding dressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All cum 2.2 Providing & laying cement concrete 150mm thick (1:4.8), 40 mm agg. excluding the cost of centering & shuttering - 150mm thick 2.3 Providing & laying cement concrete 150mm thick (1:4.8), 40 mm agg. excluding the cost of centering & shuttering (10m work), including strutting, propping, etc and removal of formwork. 2.4 Providing & laying cement concrete 10					
Excavation in foundation transformer Plinth - 2nos. Excavation in foundation transhes or drains not exceeding 1.5m in width or area 1 losq m on plan, including dressing & ramming, disposal of surplus soil with in 50m lead & 1.5m lift-llard soil 2.2 Fillingoffrenches, sidesoffoundationsetc inlayers<200mmusingselected excavated cum 0.06 2.3 Providing and laying land packed stone filling or soling with stones 2.4 Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level. 1:3.6 (1 cement: 3 sand: 6 graded crushed rock 20 mm nominal size) 2.5 Providing & laying prosition reinforcedeementconcreteexcludingthecostof centering shut teringandreinforcement-allworkuptoplinth level 2.6 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 2.7 Providing & Riving centering and shuttering (formwork), including strutting, propping et. and removal of formwork 2.8 Providing & Riving centering and shuttering (formwork), including strutting, propping et. and removal of formwork 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, bending blinding and placing in position complete 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, fixing and appl. priming coal of red lead paint 2.1 Supplying/collection and stacking of stone agergeate-20 mm sq.m 19.28 2.1 Supplying/collection and stacking of stone agergeate-20 mm sq.m 19.28 2.1 Supplying/collection and stacking of stone agergeate-20 mm sq.m 19.28 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm					
Exeavation in Foundation tranches or drains not exceeding 1.5m in width or area 10sq m on plan, including dressing & ramming, disposal of surplus soil with in 50m lead & 1.5m lift-1lard soil 2.2 Erillingoftrenches, sidesoffoundationsete, inlayers<200mmusingselected exeavated cum 0.06 2.3 Providing and laying Iland packed stone filling or soling with stones Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level. 1:36 (1 cement : 3 sand : 6 graded crushed rock 20 mm nominal size) Providing& laying inpositionreinforcedcementconcrete excluding the cost of centering shut circingandicinforcement-allworkuptoplinth level Providing& laying Random Rubble Masonry with hard stone in foundation & plinth in MI : 5 Eringandicinforcement-allworkuptoplinth level Providing & Ising centering and shuttering (formwork), including strutting, propping etc. and removal of formwork Providing& fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork Providing& fixing Thermo- MechanicallyTreatedreinforcementbar(YieldStrength500MPa)forR.C.C.Workincluding cutting. Pending binding and placing in position complete Steel work welded, in built up sections, trusses, frame-works including cutting. Pending binding and placing in position complete Steel work welded, in built up sections, trusses, frame-works including cutting. Pending binding and placing in position of place and stacking of stone aggregate-20 mm sq.m 19.28 Excavationifoundation renchesor/ariansnotexeedening. Sminwidthorarea10sq.monplan,includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost			No	2.00	
2.2 Fillingoffrenches.sidesoffoundationsetc.inlayers<200mmusingselected excavated carth. ramming etc. within lead 50 m & lift 1.5m		Exeavation in foundation tranches or drains not exceeding 1.5m in width or area 10sq.m on plan, including dressing & ramming, disposal of surplus soil with in 50m	cu.m	7.08	
Providing and laying Hand packed stone filling or soling with stones Providing and laying in position plain cement concrete excluding the cost of centering and having in position plain cement concrete excluding the cost of centering and shuttering - 14ll work upto plinth level. 1:3:6 (1 cement: 3 sand: 6 graded crushed rock 20 mm nominal size) Providing& layinginpositionreinforcedcementconcreteexcludingthecostofcentering, shut the cost of centering and shuttering formwork plinth level 2.6 Providing& laying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 2.7 Providing& fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork Providing& fixing Thermo- A sum and the cost of centering and placing in position complete 2.8 Mechanically Treadedrein forcementbar(YieldStrength500MPa)forR.C.C.Workincluding cutting, bending, binding and placing in position complete 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, hosting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq.m 19.28 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq.m 19.28 Excavationinfoundation trenchesordrainsnotexeededing L.Smithwidthorarea10sq.monpla n.includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering 150mm thick may be cost of centering & shuttering 150mm thick (1:4:8), 20 mm agg, excluding the cost of centering & shuttering 150mm thick (1:4:8), 20 mm agg, excluding the cost of centering & shuttering form work), including strutting, propping, etc and removal of formwork. 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering form work), including strutting, propping, etc and removal of formwork. 2.5 Providing & fixing centering and shutt	2.2	Fillingoftrenches.sidesoffoundationsetc.inlayers<200mmusingselected excavated	cu.m	0.06	
Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level. 1:3:6 (1 cement : 3 sand : 6 graded crushed cu.m. 0.56 rock 20 mm nominal size) 2.5 Providing & laying inpositionrein/forcedementconcreteexcludingthecosto/fcentering, shut teringandrein/forcement-allworkuptoplinth level 2.6 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 2.7 Providing & lixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork 2.8 Providing & fixing Thermo- Mechanically/Treatedrein/forcementbar(YieldStrength500MPa)forR.C.Cworkincluding cutting, bending, binding and placing in position complete 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, hoisting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone agergeate-20 mm sq.m 19.28 F Construction of chain link fence (10mX10m) with gate - Znos. Excavationin/foundationtrenchesordrainsnotexeedengls_Simiwidthorarea10sq.monplanicludingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick may be cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg, excluding t	2.3		cu.m	0.74	
2.5 Providing & laying inpositionreinforcedeementconcreteexcluding thecost of centering and tering and reinforcement-allworkuptoplinth level 2.6 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth in CM 1:5 2.7 Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork 2.8 Providing & fixing Thermo-Mechanically Treatedreinforcementbar(YieldStrength500MPa)forR.C.Cworkincluding kg 68.06 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, hoisting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq.m 19.28 Excavationinfoundationtrenchesordrainsnotexceeding 1.5minwidthorarea 10sq.monpla n,includingdressing & ramming, disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering - 150mm thick (1:3:6), 20 mm agg., excluding the count of centering & shuttering - 150mm thick (1:3:6), 20 mm agg., excluding the count of centering & shuttering formwork. 2.5 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the count of centering and shuttering (form work), including strutting, proping, etc and removal of formwork. 2.6 Providing & fixing C1 chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 Steel work in welded se		Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - All work upto plinth level. 1:3:6 (1 cement : 3 sand : 6 graded crushed		0.56	
in CM 1:5 2.7 Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork Providing& fixing Thermo- MechanicallyTreatedreinforcementbar(YieldStrength500MPa)forR.C.Cworkincluding cutting. bending.binding and placing in position complete 2.9 MechanicallyTreatedreinforcementbar(YieldStrength500MPa)forR.C.Cworkincluding cutting. kg 68.06 cutting.bending.binding and placing in position complete 2.9 Stel work welded, in built up sections, trusses, frame-works including cutting. kg 46.28 hoisting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq.m 19.28 Excavationinfoundationtrenchesordrainsnotexceeding1.5minwidthorarea10sq.monpla n.includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.1 n.includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering form with hard stone in foundation & plinth - In cu.m 11.12 2.1 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering form work), including strutting propping, etc and removal of formwork. 2.4 Providing and fixing centering and shuttering (form work), including strutting. 2.5 Providing & fixing GI chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) -3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels.	2.5	Providing&layinginpositionreinforcedcementconcreteexcludingthecostofcentering, shut	cu.m	1.56	
etc. and removal of formwork Providing& fixing Thermo- Mechanically Treatedreinforcementbar(YieldStrength500MPa)forR.C.Cworkincluding cutting, bending, binding and placing in position complete Steel work welded, in built up sections, trusses, frame-works including cutting, hoisting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq.m 19.28 F Construction of chain link fence (10mX10m) with gate - 2 nos. Excavationinfoundationtrenchesordrainsnotexceeding I.5 minwidthorarea10sq.monpla n,includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5 m lift-All types of Soil 2.1 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick 2.3 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In Cu.m 11.12 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.6 Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples 2.7 Steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.6	in CM 1:5	cu.m	4.22	
2.8 MechanicallyTreatedreinforcementbar(YieldStrength500MPa)forR.C.Cworkincluding cutting, bending, binding and placing in position complete 2.9 Steel work welded, in built up sections, trusses, frame-works including cutting, hoisting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone aggregate-20 mm sq.m 19.28 F Construction of chain link fence (10mX10m) with gate - 2nos. Excavationinfoundationtrenchesordrainsnotexceeding 1.5minwidthorarea10sq.monpla n,includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.1 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick 2.2 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. 2.6 Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 Steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Rg 46.28 46.2	2.7		sq.m	3.88	
hoisting, fixing and appl. priming coat of red lead paint 2.10 Supplying/collection and stacking of stone aggregate-20 mm F Construction of chain link fence (10mX10m) with gate - 2nos. Excavationinfoundationtrenchesordrainsnotexceeding1.5minwidthorarea10sq.monpla n,includingdressing&ramming,disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick 2.3 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.8	MechanicallyTreatedreinforcementbar(YieldStrength500MPa)forR.C.Cworkincluding cutting, bending, binding and placing in position complete	Kg	68.06	
F Construction of chain link fence (10mX10m) with gate - 2nos. Excavationinfoundationtrenchesordrainsnotexceeding 1.5minwidthorarea 10sq.monpla n,includingdressing&ramming,disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick 2.3 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.9	hoisting, fixing and appl. priming coat of red lead paint	kg	46.28	
Excavationinfoundationtrenchesordrainsnotexceeding1.5minwidthorarea10sq.monpla n,includingdressing&ramming.disposal of surplus soil within 50m lead & 1.5m lift-All types of Soil 2.2 Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick 2.3 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.10	Supplying/collection and stacking of stone aggregate-20 mm	sq.m	19.28	
Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the cost of centering & shuttering -150mm thick 2.3 Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Rum 3.24 2.4 cu.m 3.24 2.4 cu.m 11.12 2.44 2.5 Providing & fixing centering and shuttering (form work), including strutting, sq.m 19.98 2.6 Excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 Steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels.		Excavationinfoundationtrenchesordrainsnotexceeding 1.5minwidthorarea 10sq.monpla n,including dressing & ramming, disposal of surplus soil within 50m lead & 1.5m lift-All larges of Soil	cu.m	12.16	
Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5 2.4 Providing & laying cement concrete 100mm thick (1:3:6), 20 mm agg., excluding the cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.2	Providing & laying cement concrete 150mm thick (1:4:8), 40 mm agg., excluding the	cu.m	3.24	
2.4 cost of centering & shuttering 2.5 Providing and fixing centering and shuttering (form work), including strutting, propping, etc and removal of formwork. 2.6 Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.3	Providing & laying Random Rubble Masonry with hard stone in foundation & plinth - In CM 1:5	cu.m	11.12	
propping, etc and removal of formwork. Providing & fixing G.I chain-link mesh including fixing of post or struts, G.I staples (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92		cost of centering & shuttering	cu.m	2.44	
2.6 (excluding the cost of posts/struts, earthwork, concrete etc.) - 3.15mm (8 SWG)x50mm 2.7 steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels. Kg 801.92	2.5	propping, etc and removal of formwork.	sq.m	19.98	- F)
coat of red lead paint/bitumen coating In flats, Tees, angles and channels.		(excluding the cost of posts/struts, earthwork,	sq.m	144.00	
2.8 Providing & fixing bolts of various sizes including nuts & washers Kg 14.80	2.7	steel work in welded section including cutting, hoisting, fixing and applying primary coat of red lead paint/bitumen coating In flats, Tees, angles and channels.	Kg	801.92	
	2.8	Providing & fixing bolts of various sizes including nuts & washers	Kg	14.80	



2.9	Providing & fixing G.I barbed Wire Netting including fixing of post or struts, G.I staples, coal taring in case of ballies complete (posts/struts, earthwork, concrete paid separately) - 2.5mm, (12 SWG), 4 barbs form by twisting two point wires, each two turns, pitch of barbs 100mm	m	320.00		
2.10	Substation gate fabricated out of M S angle section 4m wide, 2m high with 2 leafs opening with all locking arragement as per BPC standard.	No	2.00		
G	Construction of RMU foundation				
1	Earthwork in excavation over areas, depth >300mm, width >1.5m, area >10 Sq.m on the plan, including disposal of excavated earth within 50m lead and 1.5m lift & disposed of soil to be neatly dressed-All types of soil	cu.m	3.91		
2	Filling of trenches, sides of foundations etc. in layers <200mm using selected excavated earth, ramming etc. within lead 50 m & lift 1.5m	cu.m	2.78		
3	Providing & laying in position reinforced cement concrete excluding the cost of centering, shuttering and reinforcement - all work upto plinth level - all work upto plinth level in 1:1.5:3 (1 cement : 1.5 sand : 3 graded crushed rock 20 mm nominal size)	cu.m	1.30		
4	Providing & fixing Thermo-Mechanically Treated reinforcement bar (Yield Strength 500 MPa) for R.C.C work, including cutting, bending, binding and placing in position completely.	cu.m	29.68		
5	Providing & fixing centering and shuttering (formwork), including strutting, propping etc. and removal of formwork - Foundation and plinth etc.	sq.m	13.52		
6	Providing and laying in position plain cement concrete excluding the cost of centering and shuttering - 1:2:4 (1 cement : 2 sand : 4 graded crushed rock 20 mm nominal size)	cu.m	0.62		
7_	Steel work in single section including cutting, hoisting, fixing, welding and applying priming coat of red lead paint	kg	66.12		
Sub-Total for II					
	Total Amount				
Rebate	Rebate				
In words					
Mater					

Note

The quantities mentioned here are indicative and are estimated values. These are subject to change at the time of execution. Payments shall be made based on the actual volume of works at the rate or price schedule of the contract.

